

Your link to integrated analyses !

TRANSPORT & MOBILITY LEUVEN VITAL DECOSTERSTRAAT 67A BUS 0001 3000 LEUVEN BELGIUM

http://www.tmleuven.be/

TEL +32 (16) 31 77 30 FAX +32 (16) 31 77 39

Transport & Mobility Leuven is a cooperation between the Belgian University K.U.Leuven and the Dutch research institute TNO.

# An empirical agent-based model of parking behaviour

Authors: Karel Spitaels, Sven Maerivoet

30 June 2008

Paper presented at the Kumho-Nectar conference 2008 on "Transport and urban economics".

#### <u>Abstract</u>

Today, many cities are faced with parking problems, which are only expected to become worse. Yet, there exists little empirical and theoretical knowledge on the parking behaviour of the drivers. However this knowledge is essential in order to estimate economic, social and environmental impacts of new or changing parking policies in a city.

In this paper we develop the microscopic, agent-based simulation model SUSTAPARK (SUSTAinable PARKing). At its core is a heuristic model of the parking behaviour and strategic decisions of drivers. The decision model captures reactions of the drivers to changes in the time available to them and to the local situation on the road. The model also takes into account the individual preferences of the drivers. Their main strategic decisions include aspects such as the choice between an on-street or off-street parking place, as well as choices like 'I will make another lap around this block' or 'I will now look in the next side street'.

The decision rules are constructed with a parsimonious set of variables, incorporating the value of time and the willingness to cheat. The constructed model can be used to formulate parking management strategies that optimise the overall search time for and the use of parking places.

#### Keywords

parking strategy, agent-based modelling

# An empirical agent-based model of parking behaviour

Authors: Karel Spitaels, Sven Maerivoet 30 June 2008

# 1. Introduction

Today, many cities across the world are faced with substantial parking problems. Drivers arriving with their automobiles near the location of their desired activity need to park. Usually they wish to do so near this location. Yet, with the current level of automobile usage most cities simply cannot provide enough parking spaces to meet the demand of every driver coming to the city. Worse still, the number of trips made by car is expected to rise even further, implying an even greater demand for parking and therefore larger parking problems.

In recent years, policy makers and advisory groups thought of a wide variety of measures to alleviate parking problems. An overview of such measures was made by the Victoria Transport Policy Institute [Lit2006a]. Some suggested measures are park-and-ride, carsharing, ridesharing, correct parking pricing, car-free districts, special event management... The economic, social and environmental effects and the efficacy of these measures are not known for most of the (proposed) measures. This knowledge would allow policy makers to more effectively work on solving the parking problems and the associated mobility problems.

This paper presents a behavioural model for parking developed in a project that studies the many aspects and impacts of parking. The structure of the paper is as follows: first a literature overview on parking is presented, secondly a description of the project is given to give the context of the behavioural model, and then the actual model is described. Some simulation results of the model are presented, followed by directions for further research. Lastly, we present some concluding remarks.

#### 2. Literature overview

Parking first became a problem around 1930 when rising levels of automobile ownership made it impossible that every driver parked at the curb. Policy makers then came up with what seemed (and was) a wonderful solution at the time: minimum parking requirements. New buildings in cities were obliged to provide a minimum of on-street parking spaces. Where land was cheap, as in the United States, this resulted in a feedback loop where plentiful parking space encouraged car usage which led to more emphasis on providing parking space (contributing significantly to the phenomenon of 'urban sprawl') [Sho2005].

In the older, already densely built cities of Europe, but also in some older cities in the United States, like New York, providing plentiful off-street parking places was and is often not possible. This contributed to companies relocating to the periphery if accessibility could not be achieved by some other means, such as a well-developed public transport system [Sho2005]. It should be noted that the responsibility for parking requirements usually lies at the municipal level, leading to a wide array of parking requirements, adjusted to suit the local needs [Hea1992]. The justification for these requirements is not known or unclear. The Institute of Transportation Engineers does have a publication 'Parking Generation' [ITE2004] that forms the world's largest collection on data for parking demand at buildings of various sizes and purposes. Shoup questions the reliability of these figures and decries the misuse of them by city planners [Sho2002].

Problems associated with parking in the twenty-first century include additional congestion, emissions, noise and a decrease in the liveability of neighbourhoods as a consequence of drivers cruising for parking. Also, providing parking places means the consumption of expensive, scarce land. Parking shortages can also result in cities gaining a reputation for poor accessibility, causing shoppers, tourists and commuters to stay away and eventually businesses to leave the city.

As parking is strongly connected to other systems of a city, most notably the transportation system and land use, its 'performance' and usage spreads throughout the entire fabric of the city. Parking revenues can be used to fund street works, increase police surveillance and many other measures that increase the attractiveness of the city. A good functioning parking system is a major attraction point for a city, leading to more businesses coming to the city and

therefore to more workplaces. Decreasing parking problems also means a reduction in congestion, emissions, noise and visual hindrance. It also means a reduction in the time lost searching for a parking place and an increase in the liveability of the city.

Because solutions to parking problems take time to implement, which might lead to a changed situation by the time the policy becomes operational, care should be taken that the new policies contribute to the economic, social and environmental goals of the sustainable city. Parking problems and their direct effects form only a part of the mobility and sustainability problems that cities face today. Research into and solutions for parking problems should not happen independently from the rest of the transportation system in the city.

Despite the relevance of the issues raised by parking problems and the fact that the average automobile is parked 95% of a day (or about 23 hours each day), scientific interest in parking and its economic, social and environmental aspects has been intermittent at best, and certainly low in comparison to the attention topics such as road pricing have received. One reason road pricing is more interesting from a theoretical point of view is that it can be used to influence a much larger group of externalities than parking policies can [Mar2006]. In recent years interest in parking has increased, as shown by the publication of books by Litman [Lit2006b] and Shoup [Sho2005] and the publication of a special issue of Transport Policy on parking. This issue contains, among other articles, a good review of the current literature on parking policies [Mar2006] and an article on cruising for parking [Sho2006].

There exists little empirical knowledge of the parking behaviour of drivers. For example, it is not known how many drivers in cities are cruising for parking, let alone how this number varies during the day or what the relation, if any, is with the local circumstances. Journalists frequently city a figure of about 30 percent, a figure that likely originated from the research in the United States of Shoup. However, this figure is an average over multiple studies that often produced widely differing results and took place in a time span of more than 70 years [Sho2006]. As Shoup himself notes [Sho2005], these studies are probably not very good and likely underestimate the amount of cruising for parking. The circumstances surrounding parking, such as traffic volume and the availability of parking places, changed substantially in this time. Also, the study locations cannot be considered to have been free of bias. The comparability of these studies with each other and the representativity of their results is

therefore doubtful. Still, these studies do indicate that cruising for parking can contribute substantially to traffic in the city.

Theoretical research into parking was performed mostly in the field of economics. Most authors consider parking pricing as a means either to internalise search externalities or to set an optimal price if road use is underpriced. The most advanced of these models include onstreet and off-street parking and traffic congestion [Cal2002, Arn2007]. Older models consider only one or two of these aspects [Cal2004]. The aggregate, macro-economic methods applied can be criticised, however. They mostly ignore the local nature of parking and the heterogeneity in purpose and characteristics of the driver coming to the city. They also assume that the government has perfect instruments, while ignoring the high cost of (necessary) enforcement for on-street parking. While parking policy is often intended to lessen car pressure by indirectly encouraging non-car modes of transport [Mar2006], no attention seems to have been paid to this aspect in the economic literature.

In the economic models that take congestion on the road network of a city into account, it is not clear what is meant by a 'congested' street network. The conventional definition of congestion is that the travel time on the road is higher than what is normal for that road. However, in transportation engineering it is known that traffic in a city is almost fully determined by delays at crossroads and intersections [Mae2006]. If parking is taken into account, additional delays are caused by drivers looking to park and drivers parking or unparking. It is therefore not at all clear what congestion means in a city, as the primary cause of delays is an inherent part of the normal travel time.

In the field of traffic engineering parking has gathered some interest also. An overview of the research in this field can be found in [You2000]. The most notable contribution was the PARKSIM model of Thompson and Young [You1986, You1987a, You1987b], which models in great detail the behaviour of parkers in parking lots and is intended to aid in the design of new parking lots. Young [You2000] distinguishes 5 types of parking models, namely parking-design models, parking-allocation models, parking-search models (both in parking lots and in a street network), parking-choice models and parking-interaction models. He concluded that in all of these types of models more emphasis should be placed on the assessment of urban parking policies and the behavioural response of parkers to them.

We conclude this literature overview with a quote from Marsden [Mar2006]: "We do not understand nearly enough about how individuals respond to parking policy interventions nor how these responses interact with local circumstances, the availability of alternative transport modes or alternative destinations. A continued failure to take on the research challenges in this area will surely see increased degradation of the residential environment and further imbalances in supply and demand in a variety of locations for work, shopping and leisure trips. Parking policy may not be theoretically appealing but it is practically essential." The following section describes a project intended to improve the understanding of parking and to allow the simulation of parking policies.

# 3. SUSTAPARK project summary

SUSTAPARK is a project in which various parking and mobility policies are researched and modelled. One of the main objectives of the project is the development of a city-level model for parking. This model and its results are intended to support policy makers in their decisions concerning parking and mobility. Such aspects include the optimal parking fee, the determination of the parking needs at a location and the impact of a new parking garage. From the beginning of the project it was decided that special attention would be paid to onstreet parking (also known as curb parking) and its related aspects. An important aspect of onstreet parking is the search behaviour of a driver looking to park on-street. To properly model this, an agent-based approach was chosen.

Because the search to park of an individual is a phenomenon on a local level, a microscopic modelling approach was chosen for the physical movements of the cars. A microscopic approach also integrates more naturally with an agent-based approach than a macroscopic approach. The microscopic simulation methodology adopted was that of the cellular automaton, in which time and space are discretised. By dividing the individual road lanes into cells with a certain width and length a representation of the real street network is obtained that is still understandable and computationally fast.

The SUSTAPARK model itself is a simulator of the decisions that persons take concerning their mobility throughout the day. Since the search for parking of an individual is a phenomenon on a local level, it was chosen to simulate the streets and the traffic in cities with a cellular automaton. A cellular automaton is a simulation technique in which space is discretised in cells and time is discretised in time steps. This technique has the advantage over continuous approaches of computational efficiency while maintaining a sufficient degree of accuracy [Mae2006]. In the SUSTAPARK model the individual road lanes are divided along their length in cells such that a representation of the road network is obtained. To this street network on-street parking places, parking garages and locations can be attached.

The agents in this model want to be at certain locations at certain times, providing the motive for transportation. Depending upon characteristics of the agents themselves, the different transport modes available and the desired destination the agents make a choice regarding the mode of transportation and, if the car was chosen as the transportation means, the intended parking location or strategy to look for one. In the case of on-street parking, the model contains an elaborate modelling of the way people look for a parking place.

The SUSTAPARK model runs a simulation for an entire day and collects various statistics regarding parking and mobility in the city. Through the setting of various policy-related variables scenarios can be analysed and policy makers can use it assess the impacts of various policies.



**Figure 1:** Choice tree of the behavioural component. The two boxes indicate the 2 separate model parts; the upper box contains the model that determines the initial parking strategy, the lower box indicates the model that is used to find a parking place.

# 4. Parking behaviour model

#### 4.1 Determinants of parking behaviour

Through literature study and interviews several variables were identified to be of potential relevance for the parking behaviour of persons. Unfortunately, in our project only a limited budget is available for data collection. The available datasets on parking, i.e. that link parking behaviour to personal characteristics, are few and far between. Because of this lack of data it is not possible to use all of the variables listed below. It should also be noted that some of the variables listed below are difficult to measure in practice.

- Price of the parking place: aside from supply constraints, the price of a parking place is the main policy instrument available to steer the behaviour of drivers.
- Income: income will be strongly correlated to the willingness to pay for several aspects of parking and to the value of time. Therefore it should not enter the (statistical) models directly.

- Value of time: in choosing a parking strategy, a driver will take his expected travel time into account. This is modelled through the value of time, which can be depend upon the trip purpose and can be different depending upon the activity (e.g. walking, driving, searching, waiting...).
- Trip purpose: It is well known in the field of transportation research that the choices people make regarding transportation are strongly dependent upon the purpose of the trip they want to make. The same dependency is expected for parking.
- Guaranteed parking: if a driver knows he has a parking place available somewhere (provided by his employer, for example) then he has no need to look for an on-street or off-street parking place.
- Occupancy ratio: In some areas of a city a driver might expect that there is only a low chance of finding a parking place around a specific time. The driver might choose to avoid a long expected search time or the risk of not finding a parking place and instead choose another means of transport or parking.
- Parking capacity: the driver can take into account the amount of parking places in an area, both on-street and off-street.
- Turnover rate: on-street parking places are rarely occupied by the same vehicle for the entire day and even not for a large part of the day. In the city centres there is a fairly high turnover rate as drivers park and unpark, which makes the strategy of circling around the block worthwhile.
- Dummies: Regardless of the amount of variables in a model, there will always be unobserved factors. These can be captured through the use of dummies. An example of an unobserved factor is the bias against parking in an (underground) parking garage that many drivers have.
- Travel time: The expected travel time will be dependent upon many factors, but for parking the proportion of the time spent on parking in relation to the total travel time is one of the more relevant attributes.
- Search time: The time that a driver has spent searching for a parking place or expects to spend on searching for one. This variable has correlations with the value of time and the occupancy ratio.
- Remaining time: If a driver has a limited time budget, if he has an appointment, for example, then he will keep a close eye on the time that he has still available.

- Switching distance: The distance from his destination at which a driver starts to look for an on-street parking place. Depending upon further research this might have to be implemented as a switching time instead of a distance.
- Fine and fining probability: on-street parking policies relying on drivers paying the right price necessitate enforcement of these policies (it is assumed that drivers always pay the correct price for off-street parking). Drivers might therefore choose on-street parking if they value the expected fine (fining probability times the actual fine) to be low.

Some of these variables will be more relevant for the search for an on-street parking place, others will be more determining for the initial choice between on-street and off-street parking. If possible, attention should be given to the interactions and correlations between the variables, especially when they are included in discrete choice models.

#### 4.2 Methodology

In reality many decisions taken regarding transportation are taken simultaneously. This is not feasible in the modelling of transportation, so the different choices to be made are modelled as sequential choice processes. A sequence frequently adopted is first the generation choice [Bel2006] (the decision whether to make a trip) and then consecutively the destination choice, the mode choice model, the choice of departure time and the choice of the route taken to the destination. In the SUSTARK model the generation choice, the destination choice and the choice of departure time are not modelled. Especially the departure time choice is currently a topic of much research. In a further development of the model it might be added, as time-dependent parking policies can have the effect of causing a shift in the time of departure. The model assumes that all agents active in the model will have the desire for transportation at some point.

Instead, the trip generation, the destination and time of departure choice are determined for each agent from one of a set of possible activity schedules. Such an activity schedule describes for a representative person the sequence of locations the agent wishes to be at from a start time to an end time. A schedule covers an entire day of an agent from around 3 AM to 3 AM the next day. This allows simulating the various sources of parking demand throughout

the course of a day and can be differentiated for different days of the week, such as work days and weekend days. Possible types of schedules are

- commuter who comes from outside the city to work in the city.
- resident who goes to work either inside or outside the city and needs to return home in the city in the evening.
- shopper who comes to the city as a centre of commerce.
- entertainment seeker who comes to the city for leisure.

The time of departure is derived from the start time of the activities by adding the expected travel times and search times for a parking place.

The behaviour model in SUSTAPARK determines the mode choice and the search behaviour of drivers looking to park. The outline given in the previous part separates in two choice models, one model that determines mode choice and the intended parking strategy before the driver starts looking for a parking place and another model that executes the parking strategy of the driver as he is looking for a parking place. This last model requires the ability to re-evaluate the current strategy and, if necessary, the change to a different strategy. For example, a driver who has unsuccessfully searched for an on-street parking place for some time might decide to go for an off-street parking place. The two models both have a part where a parking strategy is determined. These parts can be different because the determinants in the two cases can be different; the attributes relevant for the choice beforehand and the choices during the search for a parking place are not necessarily the same.

The preferred methodology for the mode choice model would be a mixed multinomial logit model. This type of model allows for random taste variation, unrestricted substitution patterns and correlation in unobserved factors over time [Tra2002]. This flexibility is achieved by defining the choice probabilities as integrals of standard logit probabilities over a density of parameters. Any distribution can be chosen for the distribution of a coefficient. However, this type of model is not suitable for the project because its flexibility comes at the cost of much greater computational requirements. The estimation and application of the nodels rely on simulation because the integrals over each distribution of parameters have to be evaluated each time a choice is made by an individual. While the computational requirements are acceptable in small-scale studies, they are too large for a simulation of thousands of agents [Hes2007].

Therefore, the methodology adopted is that of the nested logit model (also known as a hierarchical logit model) [Ben1973], which has closed form solutions. By grouping similar alternatives in 'nests' this type of model simulates a sequential choice structure. For a detailed discussion of this type of model, see [Tra2002]. The nested logit model has been used in many models to forecast travel demand and mode choice. Because the mode choice in this paper has been reduced to the choice of parking strategy, the nested logit model simplifies to the well-known multinomial logit model.

The structure of the choice tree is shown in figure 1. The upper box shows the model that is used to determine the mode choice; the lower box the model used to search for a parking place in the model. The upper tree first contains a choice between slow modes, mass transit modes and the car. If the car is chosen as mode of transportation, three types of parking are available:

- Guaranteed parking means that the driver is guaranteed a parking place at his destination. This might be because he gets a parking place from his employer, owns a garage nearby or has reserved a place in some way.
- Off-street parking is parking in a parking lot or a parking garage (either below or above ground). If this option is chosen, a specific parking garage still needs to be chosen.
- On-street parking means curb side parking, including illegal parking or parking without paying the required fee. If this option is chosen, the driver knows beforehand that he will have to look for a parking place. Consequently, he will need some strategy to find an on-street parking place. Before he starts on his trip, he will also need some notion of where he will start looking for a parking place.
- Illegal parking covers parking on all sorts of places where one is not allowed to. In some cities this can be a large amount of the number of parked cars. Illegally parked cars contribute more than other cars to visual obstruction, create unsafe situations and prevent land from being used for its intended purpose. An illegally parked also does not pay the actual cost for his parking place, thereby passing this cost on to the rest of society. Here, illegal parking also covers cars parked at a legal place, but not paying the fee for it.

13

Few authors consider the aspect that enforcement of the parking fee for on-street parking is costly and requires substantial amount of manpower. (It is assumed that off-street parking is always paid) In some cities enforcement is strict, but in other cities enforcement is not strict, making it worthwhile to drivers to risk not paying. Policy instruments relying on drivers paying the right price should take this aspect into account when assessing the impact and revenue of a new policy.

Depending upon the city different choices for mass transit can be available. While bus and train are the most common, other options, such as tram or metro, might also exist. Because of this and because the modelling of mass transit is not the primary focus of the project, mass transit and slow modes are not explicitly modelled. Instead their shares are exogenously given. This does mean that the upper model reduces to a simple multinomial logit model for the choice between the different types of parking place.

The model must also be capable of modelling novel parking schemes, like park-and-ride, that are different enough from the types of parking described above that they cannot be catalogued as one of them. Modelling of the success rates of these novel parking schemes is difficult, as this can only be done identifying the relevant choice attributes for these schemes and collecting data on them in a stated preference survey of sufficient scale (see, for example, [Alb2006]). These were not foreseen within our project. Therefore, the success rate of a new parking mode will also need to be exogenously given. A side effect is that this also allows the evaluation of the effects of various success rates of a given policy since the model does not depend on one internally calculated success percentage.

#### 4.3 Pre-trip choice model

For the upper model (in effect, the model for the parking type choice) we adopt the MNL model of Hess and Polak [Hes2005]. The model makes a distinction between a 'work' purpose (commuting) and an 'other' purpose which captures all other trip purposes. This gives mainly differences in the willingness to pay for parking and to risk a fine. The multinomial logit model described here concerns a choice made before the trip is actually made. This means that the model deals with the values of the variables expected by the agents, not the observed values. This is an important distinction for the interpretation of the model.

Variable name	Work	Other
Access time [min]	-0.0513	-0.0283
Search time [min]	-0.0632	-0.0589
Egress time [min]	-0.0925	-0.0924
Parking fee [€h]	-1.4104	-0.8267
Expected fee [€]	-1.2347	-0.4228
I <sub>on-street</sub>	-2.7628	-0.8126
Ioff-street (lot)	0.2830	-0.0913
I <sub>off-street(g arage)</sub>	1.0614	-0.2140
I <sub>Illegal</sub>	-0.8833	-2.8972

**Table 1:** Table with the coefficients of the MNL model for the parking type choice [Hes2005].

The access time is the expected time to drive to the area around the destination, which is the area where the driver intends to park. The search time is the time a driver is willing to search for a parking place once he has arrived at his parking area. This will be important for on-street parking, but it could also be that the preferred off-street parking is full and that the driver has to go looking for another parking lot or parking garage. The egress time is the time a driver is willing to walk from his parking place to his actual destination. For the calculation of these times the assumption is made that the driver has full knowledge of the city, including roads, parking places and parking garages.

The parking fee is the amount of money the driver would have to pay for the time he spends at the parking place. This can be zero if the parking place is provided free to the driver. The expected fine is the actual fine times the expected probability of getting a ticket. In the article of Hess and Polak [Hes2005] this was separated from the parking fee because it was found that the fine was valued significantly different from the amount of money that had to be paid for the fee. Note that this fine lumps together both parking at a place where it is illegal to do so and parking at a legal place, but not paying for it, is not considered.

The other variables are alternative-specific constants, with the 'free on-street parking' alternative chosen as the reference level. The other dummies stand consecutively for paid on-

street parking, (paid) parking in a parking lot, parking in a (multi-storey) parking garage and illegal parking. Substantial differences can be seen between the coefficients for the 'work' purpose and for the 'other' purpose. In particular, commuters seem to have a strong dislike of paid on-street parking and seem to prefer garages. For the 'other' purpose, the willingness to park illegally is much lower than for the 'work' purpose. Hess and Polak [Hes2005] note that the signs of the dummies for parking lot and parking garage of the 'other' purpose are wrong and should in fact be positive.

#### 4.4 On-street search model

As shown in figure 1, the choices in the parking choice model described above require further modelling. The process of finding an off-street or on-street parking place is complex and not straightforward to model. The methodology adopted is explained in the following paragraphs.

The approach in the paragraphs below is partly inspired by the work of Thompson and Richardson [Tho1998]. The case treated first is that of driver looking for on-street parking. The guiding principle here is that a driver desires to park as close as possible to his destination. For most part of his trip, the driver follows the route towards his destination and he is not looking for a parking place. In case the driver expects to park in a street where there are only parking places on one side of the street, the route choice should take this into account. The driver only starts searching when he gets near enough to his destination. This distance is about 200 m from his destination, measured along the roads, not as the crow flies. This assumes that the driver knows exactly where his destination is located and the street network surrounding this location. It is possible to modify this distance if the driver perceives the occupancy ratio to be low or high.

When the driver decides to start looking for a parking place, he immediately starts to look ahead some 35 metres (roughly 6 to 7 parking places on one side of the street) for free parking places. This distance is situation dependent; if the driver is tailgating, he can only see one or two places. If the driver sees a free parking place or places, in general he prefers the one closest to his destination to park. Sometimes the parking fee will be higher in some zones of the city, which might cause drivers to avoid these parking places. If the driver does not see any free parking places, he will need to make a choice as to where he will look next. In the current version of the model, a driver looking to park ignores drivers wishing to leave a parking place.

Determining where to look next for a parking place is a complicated matter. The decision process could be modelled as a series of choices, pointing in the direction of discrete choice theory. However, discrete choice theory does not offer the needed flexibility, given the multitude of situations that can be encountered in the streets of a city. Therefore a heuristic algorithm was developed.

First, the driver re-evaluates the local situation and decides whether he should continue to look for on-street parking. For this, a logit similar to the one used to determine the initial search strategy is appropriate. The main difference lies in the interpretation of the parameters. The access time is now zero for on-street parking and illegal parking, since the driver already arrived at the area where he intended to park. The search time is now interpreted as the time the driver already spent searching; the higher this time becomes, the more likely a driver is to switch to a different parking strategy. The egress time increases with the distance that a driver gets removed from his destination. For the consideration of the nearest off-street alternatives the access time is still relevant, since the driver will have to drive towards it. The search time and the egress time still have the same meaning here.

A relevant factor is the turnover rate, more so than the occupancy ratio. If the driver observes the turnover rate to be low, it is less useful for him to keep looking for an on-street parking place. No information on the turnover rate and its valuation by the drivers is known to us, however.

If he decides to continue looking for an off-street parking place, he will need a route to his next search location. In the model developed by Thompson and Richardson [Tho1998], this could be determined fairly simple due to the hypothetical CBD that was used being composed of square blocks. Our model has to be capable of modelling the inner areas of the European cities with their complex winding streets. Generally, a driver will search for an on-street parking place in an area around his destination with a radius that increases the longer the driver cruises looking for parking. This radius can increase to 550 m at maximum [Gan2006]. Note that actual decisions as to where to look next only need to be made at intersections and crossroads. Otherwise, a driver has no other option than to continue driving down the street he

is in. The model does not allow a driver to change his driving direction in a street. This because this is often not feasible in the streets of an European city and because it is likely that the parking place will already be occupied by the time the driver has changed directions.

At an intersection, the driver can evaluate the apparent occupancy ratio in all the streets that connect to the intersection. If the occupancy ratio is substantially lower in one of the streets, the driver will chooses that street to look next for parking. This mechanism will, by its nature, quickly result in streets where the occupancy ratio is roughly equal in the immediate area of a driver. The occupancy ratio will vary across a city dependent upon the number of destinations within an area.

If the occupancy ratio is about equal in all the streets, the drivers adopts the 'circling around the block' strategy where he circles around the block one or more times in the hope of finding a free parking place at the block or that a place will be vacated in the time it takes him to make a tour around the block. If this fails, the driver starts looking in an area around his destination, making laps of which the radius increases the longer he cruises for parking. It should be noted that this strategy can fail, as the driver might wind up in a traffic situation where it is impossible for him to make the tour around the block he intended, due to one-way streets for example. In that case the driver tries to get back to his destination along the most expedient route available (remember that a driver is assumed to have full knowledge of the street network).

If a driver decides to go for an off-street parking place, his search strategy is different. While on-street parking can be regarded as a roughly continuous quantity spread out across the city, off-street parking is inherently discrete, constrained to the relatively few parking lots and parking garages available to the public. Following the same principles as for on-street parking, a driver initially selects a parking garage through a logit of which the most important variables are the distance from the garage to his destination, the price of the garage and the expected amount of free places in the garage. If, upon arriving at this garage, it is revealed that this garage is full, the driver reroutes to the second nearest garage and so on. If in the process of driving towards a parking garage a driver notices a free on-street parking place, he can decide to take this place, but he does not actively look for an on-street parking place.

#### 5. Directions for further research

The most necessary is the collection of data. Few efforts have been undertaken for the collection of data regarding parking and the relevant attributes of parking. What data exists, is frequently old and likely outdated (such as the data on which the coefficients in this review are based). The socio-economic factors that are relevant for the value of time and the willingness to pay are ignored in all studies known to us. More research on how drivers actually look for a parking place is also necessary.

Further, to function as a policy model the SUSTAPARK model needs to have a model for the modal choice of the agents. One of the main objectives of various policies related to parking is to achieve a modal shift, i.e. the encouragement of the use of other means of transport than the car in order to increase the sustainability of the transportation system and the liveability of the city. This necessitates the development of a model for modal split that for the car mode also takes into account the various available parking options.

In recent years many parking policies and 'new' forms of car use, parking and parking management have been suggested. Actual implementations of these policies (aside from carpooling) have been rare and little research has been done into the efficacy and popularity of these measures. To provide good advice to policy makers, a large scale study should be performed into the attitudes of the public towards these measures. Formulating general conclusions regarding the efficacy will likely be difficult, as this depends strongly upon the details of the implementation and the local circumstances. But this is one aspect that the SUSTAPARK model intends to tackle.

# 6. Concluding remarks

This paper described a model for the behaviour of drivers needing to park. This model can be applied in the analysis of policies for the optimal usage of parking places and the reduction of the time that drivers spend looking to park. The parking behaviour of drivers is very complex and strongly dependent upon the local circumstances. Our model attempts to capture this behaviour under the restrictions of the limited data available. Policy makers attempting to influence parking behaviour need to find the right balance between providing enough parking at the correct price and providing not so much parking that car usage is excessively encouraged. Policy makers can employ two groups of tools: one group contains mostly pricing and capacity management measures that can be implemented in a short time frame; the other group contains measures that have their impact in the long term and work mainly on the supply side of parking.

But policy makers should keep in mind that trying to diminish the number of cars in the city should be paired with the development of and investment in alternative means of transport, both in their geographic coverage as in level of service. Otherwise, the city will become less accessible for everyone and those who need to be in the city will still come by car, causing problems in the city with their difficult to park car.

### Acknowledgements

This research was funded by a grant under the Science for a Sustainable Development research programme of the Science Policy of the Belgian Federal Public Planning Service. We are grateful to our project partners; the SADL department of the Katholieke Universiteit Leuven and the CRU department of the Université Libre de Bruxelles.

#### References

- [Alb2006] Albert, Gila and David Mahalel, **Congestion tolls and parking fees: a comparison of the** potential effect on travel behavior, Transport policy 13 (2006), pp. 496-502.
- [Arn2007] Arnott, R. and J. Rowse, Downtown parking in auto city, Boston College Working Papers in Economics No 665, April 2007.
- [Bel2006] Bellei, Giuseppe, Guido Gentile, Lorenzo Meschini and Natale Papola, A demand model with departure time choice for within-day dynamic traffic assignment, European journal of operational research, 175 (2006), pp. 1557-1576, 2006.
- [Ben1973] Ben-Akiva, M., The structure of travel demand models, PhD thesis, MIT, 1973.
- [Cal2002] Calthrop, E;, Evaluating on-street parking policy, ETE working paper series No 2002-03, May 2002.
- [Cal2004] Calthrop, E. and S. Proost, **Regulating on street parking**, ETE working paper series No 2004-10, August 2004.
- [Gan2006] Gantelet, Eric and Amélie Lefauconnier, **The time looking for a parking space: strategies,** associated nuisances and stakes of parking management in France, SARECO research

report, Association for European Transport and contributors, 2006.

- [Hea1992] **Internationale vergelijking parkeernormen**, study of Healey and Baker for the Dutch ministry of Transport, 1992.
- [Hes2005] Hess Stephane and John W. Polak, **Mixed logit estimation of parking type choice**, Imperial College London working paper, 2005
- [Hes2007] Hess Stephane, Andrew Daly, Charlene Rohr and Geoff Hyman, On the development of time period and mode choice models for use in large scale modelling forecasting systems, Transportation research part A 41 (2007), pp. 802-826, 2007.
- [ITE2004] **Parking Generation**, **3**<sup>rd</sup> edition, Institute of Transportation Engineers, January 2004.
- [Lit2006a] Litman, T.A., **Parking management: strategies, evaluation and planning**, Victoria Transport Policy Institute, 25 April 2006.
- [Lit2006b] Litman, T.A., **Parking management best practices**, American Planning Association, Planners Press, 2006.
- [Mae2006] Maerivoet, S., Modelling traffic on motorways: state-of-the-art, numerical data analysis, and dynamic traffic assignments, PhD thesis, KUL, 2006.
- [Mar2006] Marsden, G., The evidence base for parking policies a review, Transport Policy 13, p. 447-457, 2006.
- [Sho2002] Shoup, D.C., Roughly right or precisely wrong, University of California Transportation Center, Access 20, p. 20-25, spring 2002.
- [Sho2005] Shoup, D.C., **The high cost of free parking**, American Planning Association, Planners Press, 2005.
- [Sho2006] Shoup, D.C., Cruising for parking, Transport Policy 13, p. 479-486, 2006.
- [Tra2002] Train, K., Discrete choice methods with simulation, Cambridge University Press, 2002.
- [Tho1998] Thompson, Russel G. and Anthony J. Richardson, **A parking search model**, Transportation research part A Vol. 32 No. 3, pp. 159-170, 1998.
- [You1986] Young, W., **PARKSIM 1, a network model for parking facility design**, Traffic Engineering and control No. 27, Vol. 12, p. 606-613, December 1986.
- [You1987a] Young, W. and R. Thompson, PARKSIM 1, a computer graphics approach for parkinglot layouts, Traffic Engineering and control No. 28, Vol. 3, p. 120-123, March 1987.
- [You1987b] Young, W. and R. Thompson, PARKSIM 1, Data presentation and evaluation, Traffic Engineering and control No. 28, Vol. 5, p. 294-297, May 1987.
- [You2000] Young, W., Modeling Parking: in D. Hensher and K.J. Button (eds.), Handbook of Transport Modelling, 1, Oxford: Elsevier Science, p. 409-420, 2000.